

# 3590EGTT

3590EGTT Touch Screen weight indicator for industrial applications



Totally configurable touch screen weight indicator for advanced weighing systems. The 3590EGTT indicator, other than the chosen weighing programme, has an area for the development of specific application programmes, integrated debuggers and programming tools for PCs. Advanced weight indicator, AISI304 stainless steel with resistive touch screen display, suitable for any industrial application. It can display all of the weighing data and with the customisation of the screens, simplifying the user operations. Fitted with 3 serial ports, transmission protocols for data communication, completely configurable printouts, integrated alibi memory, and port for connection to barcode/badge reader. CE-M approvable (OIML R-76 / EN 45501).

The best solution for advanced industrial applications

#### **MAIN FEATURES**

- Resistive backlit 5,7" (120x90mm) color touch screen graphic display, suitable for use with gloves.
- Multilanguage software available in: Italian, English, German, French and Spanish. Possibility to insert a personal translation thanks to the new "CUSTOM LANGUAGE TOOL" software.
- 3-way high brightness LED crosslight.
- 15-key alphanumerical mechanical keyboard.
- Selectable QWERTY, AZERTY or QWERTZ keyboard integrated in the touch screen.
- IP68 AISI304 stainless steel case.
- Dimensions: 328x186x144 mm.
- As standard fitted with an adjustable bracket, for bench or wall mounting. Real time clock and permanent data storage.
- Supplied with alibi memory, integrated on the motherboard.
- Slot for built-in micro SD for recording the configuration, logos, and customized screens (upon request).
- Functions available with DINITOOLS Utility Software, even from remote way (WEBSERVER mode via internet).
  - Configuration, data entry and print formatting.
  - Recording and transmitting of all the information on PC.
  - Complete retrieval of the configuration.
  - Instrument calibration with numeric values.
  - Customization of the screens.
  - Development environment for custom programmes through specific programming language.
- 24-bit A/D converter, 4 channels, up to 3200 conv./sec. and up to 8 signal linearisation points.
- 4 independent analogue channels (up to 2 in the E-AF03 version) for connecting to analogue loadcells.
- Connects with up to 16 analogue load cells of 350 Ohm (45 load cells of 1000 Ohm) and with the main digital load cells available on the market (mod. E-AF03).
- Management of the most common digital load cells for weigh bridges (with DIGIKIT option and AF03GT firmware), also for CE-M
  approved applications.
- Up to 10.000e OIML or 3 x 3000e @ 0,3 µV/e CE-M legal for trade.
- Up to 1.000.000 displayable divisions for internal factory use, with internal resolution up to 3.000.000 points.
- Connectable to printers and labellers with free programming of the printout formats.
- 110-240 Vac power supply.

### **MAIN CERTIFICATIONS**

- EU Type Examination Certificate (45501:2015)
- OIML R76
- OIML R51 MID
- OIML R134 (AF09)
- NMI S788 certificate

## **APPLICATION SOFTWARE**

- AF01: Totalization and formula weighing (integrated)
- AF02: Pieces/quantity counting (optional)
- AF03: Weighbridges Input/Output vehicle (optional)
- AF04: Statistical checking of prepackaged goods (optional)
- AF05: Price compunting and industrial labelling (optional)
- AF08: Wheel and axle static weighing with 2 or various platforms (optional)
- AF09: Software for dynamic and static axle weighing with 1 or 2 platforms (optional)
- BATCH1: Single product dosage systems in loading and unloading (optional)
- BATCH: Software for multicomponent dosage systems in loading and unloading (optional, IOEXPB board must be included)


## **CUSTOMISED APPLICATIONS**

- Thanks to the integrated development area, fully customized applications can be created autonomously:
  - Specific
- weighing programmes according to customer requirements
  - Customized weighing programmes for terminal replacement in
- pre-existing systems
  - wizards, operator messages
  - serial port management, protocols customization
  - digital I/O full management
  - sequential or simultaneous automations
  - data entry, custom archives

Dini Argeo can offer the service of custom development programs.

## **CUSTOMIZABLE SCREENS**

• Thanks to the programmable Touch Screen Display, you can create custom-made interfaces for any application:



• The "Dini Display Tool" is a PC software which allows you to quickly customize the TOUCH SCREEN.







## DETAIL 3







DINI ARGEO FRANCE sarl France DINI ARGEO GMBH Germany DINI ARGEO UK Ltd United Kingdom DINI ARGEO WEIGHING INSTRUMENTS Ltd China DINI ARGEO OCEANIA Australia



#### **COMPANY HEADQUARTERS**

Via Della Fisica, 20 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 843418

#### SERVICE ASSISTANCE

Via Dell'Elettronica, 15 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE